UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.	
10/694,323	10/27/2003	Pankaj Mehra	200309900-1	3837	
	22879 7590 05/05/2008 HEWLETT PACKARD COMPANY			EXAMINER	
P O BOX 272400, 3404 E. HARMONY ROAD INTELLECTUAL PROPERTY ADMINISTRATION			FEARER, MARK D		
	FORT COLLINS, CO 80527-2400		ART UNIT	PAPER NUMBER	
			2143		
			NOTIFICATION DATE	DELIVERY MODE	
			05/05/2008	ELECTRONIC	

## Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

JERRY.SHORMA@HP.COM mkraft@hp.com ipa.mail@hp.com

	Application No.	Applicant(s)
	10/694,323	MEHRA, PANKAJ
Office Action Summary	Examiner	Art Unit
	MARK D. FEARER	2143
The MAILING DATE of this communication ap Period for Reply	pears on the cover sheet with the	correspondence address
A SHORTENED STATUTORY PERIOD FOR REPL WHICHEVER IS LONGER, FROM THE MAILING E  - Extensions of time may be available under the provisions of 37 CFR 1. after SIX (6) MONTHS from the mailing date of this communication.  - If NO period for reply is specified above, the maximum statutory period  - Failure to reply within the set or extended period for reply will, by statut Any reply received by the Office later than three months after the mailin earned patent term adjustment. See 37 CFR 1.704(b).	DATE OF THIS COMMUNICATIO 136(a). In no event, however, may a reply be ti will apply and will expire SIX (6) MONTHS fron e, cause the application to become ABANDONI	N. mely filed  the mailing date of this communication. ED (35 U.S.C. § 133).
Status		
1) ☐ Responsive to communication(s) filed on 19 F 2a) ☐ This action is <b>FINAL</b> . 2b) ☐ This 3) ☐ Since this application is in condition for allowed closed in accordance with the practice under	s action is non-final. ance except for formal matters, pr	
Disposition of Claims		
4) ☐ Claim(s) 1-17 is/are pending in the application 4a) Of the above claim(s) is/are withdra 5) ☐ Claim(s) is/are allowed. 6) ☐ Claim(s) 1-17 is/are rejected. 7) ☐ Claim(s) is/are objected to. 8) ☐ Claim(s) are subject to restriction and/or Application Papers	awn from consideration.	
<ul> <li>9)  The specification is objected to by the Examin</li> <li>10)  The drawing(s) filed on 27 October 2003 is/are Applicant may not request that any objection to the Replacement drawing sheet(s) including the correct 11)  The oath or declaration is objected to by the E</li> </ul>	e: a) accepted or b) objected or by	e 37 CFR 1.85(a). ojected to. See 37 CFR 1.121(d).
Priority under 35 U.S.C. § 119		
<ul> <li>12) Acknowledgment is made of a claim for foreign a) All b) Some * c) None of:</li> <li>1. Certified copies of the priority document</li> <li>2. Certified copies of the priority document</li> <li>3. Copies of the certified copies of the priority application from the International Bureat</li> <li>* See the attached detailed Office action for a list</li> </ul>	nts have been received. Its have been received in Applicat Pority documents have been receiv Bau (PCT Rule 17.2(a)).	ion No ed in this National Stage
Attachment(s)  1) Notice of References Cited (PTO-892)  2) Notice of Draftsperson's Patent Drawing Review (PTO-948)  3) Information Disclosure Statement(s) (PTO/SB/08)  Paper No(s)/Mail Date	4)  Interview Summary Paper No(s)/Mail D 5)  Notice of Informal I 6)  Other:	ate

## **DETAILED ACTION**

- claims 1-17 are pending in the current application.

In view of the appeal brief filed on 19 February 2008, PROSECUTION IS

HEREBY REOPENED. A new ground of rejection is set forth below.

To avoid abandonment of the application, appellant must exercise one of the following two options:

- (1) file a reply under 37 CFR 1.111 (if this Office action is non-final) or a reply under 37 CFR 1.113 (if this Office action is final); or,
- (2) initiate a new appeal by filing a notice of appeal under 37 CFR 41.31 followed by an appeal brief under 37 CFR 41.37. The previously paid notice of appeal fee and appeal brief fee can be applied to the new appeal. If, however, the appeal fees set forth in 37 CFR 41.20 have been increased since they were previously paid, then appellant must pay the difference between the increased fees and the amount previously paid.

A Supervisory Patent Examiner (SPE) has approved of reopening prosecution by signing below:

Application/Control Number: 10/694,323 Page 3

Art Unit: 2154

## Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

The factual inquiries set forth in Graham v. John Deere Co., 383 U.S. 1, 148 USPQ 459 (1966), that are applied for establishing a background for determining obviousness under 35 U.S.C. 103(a) are summarized as follows:

- 1. Determining the scope and contents of the prior art.
- 2. Ascertaining the differences between the prior art and the claims at issue.
- 3. Resolving the level of ordinary skill in the pertinent art.
- 4. Considering objective evidence present in the application indicating obviousness or nonobviousness.

Claims 1-3, 7, 9-10 and 12-17 are rejected under 35 U.S.C. 103(a) as being unpatentable over Sawada et al. (US 6907470 B2) in view of Ball et al. (US 20030046390 A1) and in further view of Futernik (US 7075886 B2).

Consider claim 1. Sawada et al. discloses a communication apparatus for routing or discarding a packet sent from a user terminal, comprising: a plurality of ports; a plurality of link up/down detection logic units, each link up/down detection logic unit associated with a port and configured to detect a change in the state of a link associated with the port (column 3 lines 8-12); however, Sawada et al. fails to discloses a configuration validation checker coupled to each of the link up/down detection logic units. Ball et al. discloses methods for construction multi-layer topological models of

Art Unit: 2154

computer networks comprising a configuration validation checker coupled to each of the link up/down detection logic units (paragraphs 0020 and 0026). Therefore, it would have been obvious for a person of ordinary skill in the art at the time the invention was made to incorporate methods for construction multi-layer topological models of computer networks comprising a configuration validation checker coupled to each of the link up/down detection logic units as taught by Ball et al. with a communication apparatus for routing or discarding a packet sent from a user terminal, comprising: a plurality of ports; a plurality of link up/down detection logic units, each link up/down detection logic unit associated with a port and configured to detect a change in the state of a link associated with the port as taught by Sawada et al. for the purpose of managing network topology changes. However, Sawada et al., as modified by Ball et al., fails to disclose a configuration validation checker that causes a switch to change its routing behavior with regard to a port for which a link up/down detection unit has detected a state change. Futernik discloses a method for routing information in satellite communication networks wherein a configuration validation checker causes a switch to change its routing behavior with regard to a port for which a link up/down detection unit has detected a state change (column 12 lines 15-64).

Therefore, it would have been obvious for a person of ordinary skill in the art at the time the invention was made to incorporate a method for routing information in satellite communication networks wherein a configuration validation checker causes a switch to change its routing behavior with regard to a port for which a link up/down detection unit has detected a state change as taught by Futernik with methods for

construction multi-layer topological models of computer networks comprising a configuration validation checker coupled to each of the link up/down detection logic units and a communication apparatus for routing or discarding a packet sent from a user terminal, comprising: a plurality of ports; a plurality of link up/down detection logic units, each link up/down detection logic unit associated with a port and configured to detect a change in the state of a link associated with the port as taught by Sawada et al., as modified by Ball et al., for the purpose of network configuration validation.

Consider claim 2, as applied to claim 1. Sawada et al., as modified by Ball et al. and Futernik, further discloses the switch wherein each link up/down detection logic unit informs the configuration validation checker when a link to an associated port becomes non-functional, and the configuration validation checker responds by discarding all packets (Sawada et al., column 1 lines 65-67 and column 2 lines 1-21).

Consider claim 3, as applied to claim 1. Sawada et al., as modified by Ball et al. and Futernik, further discloses the switch wherein each link up/down detection logic unit informs the configuration validation checker when a link to an associated port becomes non-functional, and the configuration validation checker responds by discarding all packets destined to that link (Sawada et al., column 11 lines 33-48).

Consider claim 7. Sawada et al., as modified by Ball et al. and Futernik, discloses a switch, comprising: a plurality of ports; a plurality of link up/down detection logic units, each link up/down detection logic unit (Ball et al., paragraphs 0020 and 0026) associated with a port and adapted to detect a change in the state of a link associated with the port (Sawada et al., column 3 lines 8-12); and means for causing the switch to

change its routing behavior with regard to a port for which a link up/down detection unit has detected a state change (Futernik, column 3 lines 32-56).

Consider claim 9, as applied to claim 7. Sawada et al., as modified by Ball et al. and Futernik, further discloses the switch including a means for receiving an indication from the link up/down detection logic units that a link to an associated port has become non-functional and a means for ceasing routing of all packets destined to that link (Sawada et al., column 11 lines 33-48).

Consider claim 10. Sawada et al., as modified by Ball et al. and Futernik, discloses a network, comprising: a plurality of switches coupled together; at least one end node coupled to at least one switch; wherein at least one switch includes: a link up/down detection logic (Ball et al., paragraphs 0020 and 0026) unit associated with a port and configured to detect a change in the state of the link (Sawada et al., column 3 lines 8-12); and a configuration validation checker coupled to the link up/down detection logic unit, said configuration validation checker causes the switch to change its routing behavior with regard to the port if the link up/down detection unit has detected a state change (Futernik, column 3 lines 32-56).

Consider claim 12, as applied to claim 10. Sawada et al., as modified by Ball et al. and Futernik, further discloses the network including a plurality of ports and a link up/down detection logic associated with each port, and wherein each link up/down detection logic unit informs the configuration validation checker when a link to an associated port becomes non-functional, and the configuration validation checker

responds by rejecting all packets destined to that link (Sawada et al., column 11 lines 33-48).

Consider claim 13. Sawada et al., as modified by Ball et al. and Futernik, discloses a method performed by a switch contained in a system, comprising: the switch monitoring a port for a link down event or a link up event, said link down event indicative of a link from the switch to an entity becoming non-functional and said link up event indicative of a newly established link from the switch to said entity; the switch detecting a link down event associated with said switch or a link up event associated with said switch receiving a packet into said switch (Sawada et al., column 3 lines 8-12); the switch determining if said packet is to be routed out through said port associated with the detected link down event or link up event (Ball et al., paragraph 0026); if the switch determines that the packet is to be routed out through said port associated with a detected link down event, the switch discarding the packet and if the switch determines that the packet is to be routed out through said port associated with a detected link up event, the switch routing the packet through said port (Futernik, column 12 lines 15-64).

Consider claim 14, as applied to claim 13. Sawada et al., as modified by Ball et al. and Futernik, further discloses the method including if the switch determines that the packet is to be routed out through said port associated with a detected link down event, discarding all packets received by the switch (Sawada et al., column 11 lines 33-48).

Consider claim 15, as applied to claim 13. Sawada et al., as modified by Ball et al. and Futernik, further discloses the method including requesting the entity to provide a unique identifier to the switch (Ball et al., paragraph 0075).

Page 8

Consider claim 16, as applied to claim 15. Sawada et al., as modified by Ball et al. and Futernik, further discloses the method including the switch receiving a unique identifier from the entity, comparing the unique identifier received from the entity to state information contained in the switch and, if the unique identifier from the entity does not match a value in the state information, discarding a packet destined for the entity (Futernik, Table I and column 7 lines 20-54).

Consider claim 17, as applied to claim 16. Sawada et al., as modified by Ball et al. and Futernik, further discloses the method including if the unique identifier from the entity matches a value in the state information, permitting packets destined for the entity to be routed from the switch to the entity (Ball et al. paragraphs 0062 and 0113).

Claims 4-6, 8 and 11 are rejected under 35 U.S.C. 103(a) as being unpatentable over Sawada et al. (US 6907470 B2) in view of Ball et al. (US 20030046390 A1) in further view of Futernik (US 7075886 B2) and in further view of Kao et al. (US 7054951 B1).

Consider claim 4, as applied to claim 1. Sawada et al., as modified by Ball et al. and Futernik, discloses a configuration validation checker responding to a non-functional link. However, Sawada et al., as modified by Ball et al. and Futernik, fails to disclose a configuration validation checker responding to a non-functional link notification by: receiving an identifier value from an entity coupled to the switch via the functional link; comparing the identifier value received from the entity with topology information contained in the switch; and if the identifier value matches a value in the

Application/Control Number: 10/694,323

Art Unit: 2154

topology information, permitting the switch to route packets over the functional link; or if the identifier value does not match a value in the topology information, discarding all packets targeting the functional link. Kao et al. discloses plug and play node addition in a dual ring topology network using locally significant ring identifiers for determining routing decisions wherein a check is made to determine if the topology packet was generated by the receiving node and, if so, then the topology information is evaluated and stored/updated in the topology table and, if not, then a check is made to determine if the ring identifier associated with the topology discovery packet matches the ring identifier associated with the ring on which the packet was received (("When a topology discovery packet is received (376), a check is made to determine if the topology packet was generated by the receiving node (378). If so, then the topology information is evaluated (380) and stored/updated in the topology table as appropriate (382). More specifically, entries in the topology table can be added or entries updated based on the received topology information. If the topology packet was not generated by the receiving node, then a check is made to determine if the ring identifier for the node has local significance only (384). If not, then a check is made to determine if the ring identifier associated with the topology discovery packet matches the ring identifier associated with the ring on which the packet was received (386). If no match arises, then the packet is forwarded without appending any information relating to the receiving node to the topology discovery packet (388) and thereafter the process can continue at step 376. If the ring identifier matches, then the address for the receiving node is appended to the topology packet, and as appropriate, the ring identifier associated with the ring on

Page 9

which the packet was received is appended to the topology packet as well (390). Thereafter, the packet is forwarded at step 388.") column 13 lines 51-67 and column 14 lines 1-5) and packets are discarded if an address does not match an identifier (column 12 lines 27-39).

Therefore, it would have been obvious to a person of ordinary skill in the art at the time the invention was made to incorporate plug and play node addition in a dual ring topology network using locally significant ring identifiers for determining routing decisions wherein a check is made to determine if the topology packet was generated by the receiving node and, if so, then the topology information is evaluated and stored/updated in the topology table and, if not, then a check is made to determine if the ring identifier associated with the topology discovery packet matches the ring identifier associated with the ring on which the packet was received and packets are discarded if an address does not match an identifier as taught by Kao et al. with a configuration validation checker responding to a non-functional link as taught by Sawada et al., as modified by Ball et al. and Futernik, for the purpose of effectively routing packets.

Consider claim 5, as applied to claim 1. Sawada et al., as modified by Ball et al., Futernik and Kao et al., further discloses the switch wherein said configuration validation checker receives topology information from an entity external to the switch and compares the received topology information to topology information contained in the switch (Futernik, column 14 lines 25-44).

Consider claim 6, as applied to claim 5. Sawada et al., as modified by Ball et al., Futernik and Kao et al., further discloses the switch wherein if the topology information contained in the switch does not comport with the topology information received from the external entity, preventing the newly received topology information from being used by the switch (Futernik, column 2 lines 49-67 and column 3 lines 1-8).

Consider claim 11, as applied to claim 10. Sawada et al., as modified by Ball et al., Futernik and Kao et al., further discloses the switch including a means for receiving an indication from the link up/down detection logic units that a link to an associated port has become non-functional and a means for ceasing routing of all packets (Sawada et al., column 1 lines 65-67 and column 2 lines 1-21).

Consider claim 11, as applied to claim 10. Sawada et al., as modified by Ball et al., Futernik and Kao et al., further discloses the network wherein the link up/down detection logic unit informs the configuration validation checker when the link becomes non-functional, and the configuration validation checker responds by rejecting all packets (Sawada et al., column 1 lines 65-67 and column 2 lines 1-21).

## Conclusion

Applicant's amendment necessitated the new ground(s) of rejection presented in this Office action. Any response to this Office Action should be faxed to (571) 273-8300 or mailed to:

Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450 Application/Control Number: 10/694,323 Page 12

Art Unit: 2154

Hand-delivered responses should be brought to

**Customer Service Window** 

Randolph Building 401 Dulany Street Alexandria, VA 22314

Any inquiry concerning this communication or earlier communications from the Examiner should be directed to Mark Fearer whose telephone number is (571) 270-1770. The Examiner can normally be reached on Monday-Thursday from 7:30am to 5:00pm.

If attempts to reach the Examiner by telephone are unsuccessful, the Examiner's supervisor, Nathan Flynn can be reached on (571) 272-1915. The fax phone number for the organization where this application or proceeding is assigned is (571) 273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free) or 571-272-4100.

Application/Control Number: 10/694,323 Page 13

Art Unit: 2154

Any inquiry of a general nature or relating to the status of this application or proceeding should be directed to the receptionist/customer service whose telephone number is (571) 272-2600.

Mark Fearer M.D.F./mdf April 28, 2008

/Nathan J. Flynn/

Supervisory Patent Examiner, Art Unit 2154